

SPECIFICATION SHEET: S027
AQUA-STATIC CUBICLE RANGE SYSTEMS ONE & TWO
FULLY FRAMED & SUSPENDED CUBICLE SYSTEM
K32-120 (NBS)



Detailed Product Specification

Cubicles designed to cope with the rigorous demands of high use public change areas. The design is effective through the use of rigid, aluminium heavy duty head rail sections and 50mm diameter tubular aluminium supports integrated with Solid Grade Laminate panelling.

Doors, partitions and pilasters:	Solid phenolic grade laminate, 12/13mm thick, black core. All exposed edges smoothed and radiused.
Door Latch/Indicator Bolt:	Robust easy action door latch. Emergency release facility. Large visible occupied indicator. Turn action ensures trouble free operation. Discreet security through fixings. Colour coordinated face and back plate. Vandal resistant design.
Door Hinge:	The solid grade laminate door is supported by a full length hinge bracket bonded and mechanically fixed top and bottom (middle fixing optional). Includes anti-finger trap and anti-lift design. Hinges can be adjusted so door can be allowed to stay open, close or ajar when not in use. Hinges can be fitted so doors open outwards.
Door:	Door closes against a full length sound deadening buffer. 20mm gap between the head rail and the door top to eliminate finger trap. Door corners radiused.
Coat Hook:	Single circular aluminium coat hook with integral rubber safety buffer.
Sizes:	Cubicle sizes are tailored to suit your individual requirements. However, standard overall cubicle height is 1950 mm, 900-1000mm width, with 150mm ground clearance.
Accessories:	Optional extra: Modesty panels, special fittings for disabled and family usage, baby change, wall panels etc.
Finish/Colour:	Doors and Panels: Helmsman standard SGL colour selector. Frame extrusion/hardware: Helmsman colour selector 7. – Other RAL/BS colours are available at supplementary cost. Hardware colour can match or contrast.
Frame extrusion/ Hardware/Door Furniture:	Cubicle Frame: Unique self supporting fully framed design: manufactured from heavy gauge extruded aluminium. All panels are bonded and or mechanically fixed to extrusions. Head rail top fixings are concealed with a rubber strip which stops dirt collection. All extrusions are smooth and circular which allows for easy cleaning and an excellent aesthetic appearance.
Integral Leg:	Heavy-duty 150mm high, providing 30mm adjustment to accommodate uneven floors. Concealed floor fixings.
Seat:	Solid grade laminate (hardwood slat option available for dry areas), securely fitted on 3 sides with aluminium brackets. Optional fitting via 2 epoxy powder coated 'L' brackets, manufactured from 25mm square section stainless steel. 10mm gap spacing around all edges.
Installation:	Helmsman offers a full installation service for its products.

After-sales Service: All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email service@helmsman.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.



Certificate Number FM12508



Helmsman is the trading name of
Sperrin Metal Products Ltd

1 Northern Way, Bury St Edmunds,
Suffolk, IP32 6NH, United Kingdom
Tel: (+44) 01284 727600
Fax: (+44) 01284 727601
www.helmsman.co.uk
sales@helmsman.co.uk