

## ***SPECIFICATION SHEET: S031***

### ***ECO-LINE CUBICLE RANGE SYSTEM ONE***

### ***2MM ABS EDGED CUBICLE SYSEEM***



### ***Detailed Product Specification***

**Cubicles suitable for dry change and washrooms in a package designed to provide a strong functional product at an affordable price.**

- Door and Panels: 750 density moisture resistant or standard melamine faced particle board, 18 mm thick. All edges are sealed with 2mm ABS edging to enhance the panel appearance and increase safety and durability.
- Top Rail: Angled aluminium top rail provides additional strength and stability and is bonded and mechanically fixed to fascia panels.
- Door Latch/Indicator Bolt: Robust easy action door latch. Emergency exterior opening facility. Cubicle occupied indicator. Incorporates rubber buffer for quiet door closure.
- Door Hinge: Each door fitted with 2 heavy-duty hinges, incorporating anti-finger trap and anti-lift off design. Door can be adjustable to door open/close/ajar, and open inward or out.
- Pedestal Leg: AA10 satin anodised aluminium pedestal leg 150mm high allowing 30mm adjustability for uneven / sloping floors.
- Coat Hook: Single aluminium coat hook with rubber safety buffer.
- Panel Fixings: Aluminium 'U' and angle bracket fixings for securing panels to each other and to walls. Minimum of 3 to each vertical panel. Tamper proof fixings are available as an alternative to the standard.
- Sizes: Cubicle sizes are tailored to suit your individual requirements. However, standard overall cubicle height is 1950 mm which includes 150 mm adjustable leg.
- Accessories: Optional extra: Modesty panels, special fittings for disabled, baby change, standard supply toilet roll holder. As well as cubicles the eco-Line 1 range includes co-ordinated options for Vanity Units, Wall Linings and Ducting. A wide variety of alternative hardware is available for special applications.
- Finish/Colour: Doors and Panels: Extensive colour choice from any major laminate supplier in large sheet size. Top rail/Hardware/Door Furniture - AA10 satin anodised requiring minimum maintenance. Polyester powder coating with stainless or brass finish is an optional extra.
- Seating: Changing cubicles include optional cantilever seat or standard seat bracket. Seats are made of melamine faced particle board with a 2mm PVC edge, with solid grade laminate and wood as options.
- Installation: Helmsman offers a full installation service for its products.

**HELMSMAN also provide an extensive range of lockers and changing room furniture.**

**After-sales Service:** All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email [service@helmsman.co.uk](mailto:service@helmsman.co.uk)

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.



## ***SPECIFICATION SHEET: S030***

### ***ECO-LINE CUBICLE RANGE SYSTEM TWO***

### ***ALUMINIUM EDGED CUBICLE SYSTEM***



#### ***Detailed Product Specification***

**Cubicles suitable for dry change and washrooms in a package designed to provide increased strength and durability through the application of an aluminium edging to doors and panels.**

- Door and Panels: 750 density moisture resistant or standard melamine faced particle board, 19 mm thick. All edges are sealed and enclosed within an aluminium section to provide increased protection.
- Top Rail: Angled aluminium top rail provides additional strength and stability and is bonded and mechanically fixed to fascia panels.
- Door Latch/Indicator Bolt: Robust easy action door latch. Emergency exterior opening facility. Cubicle occupied indicator. Incorporates rubber buffer for quiet door closure.
- Door Hinge: Each door fitted with 2 heavy-duty hinges, incorporating anti-finger trap and anti-lift off design. Door can be adjustable to door open/close/ajar, and open inward or out.
- Pedestal Leg: AA10 satin anodised aluminium pedestal leg 150mm high allowing 30mm adjustability for uneven / sloping floors.
- Coat Hook: Single aluminium coat hook with rubber safety buffer.
- Panel Fixings: Aluminium 'F' sections for securing panels to each other and to walls. Tamper proof fixings are available as an alternative to the standard.
- Sizes: Cubicle sizes are tailored to suit your individual requirements. However, standard overall cubicle height is 1950 mm which includes 150 mm adjustable leg.
- Accessories: Optional extra: Modesty panels, special fittings for disabled, baby change. As well as cubicles the Eco-Line 2 range includes co-ordinated options for Vanity Units, Wall Linings and Ducting. A wide variety of alternative hardware is available for special applications.
- Finish/Colour: Doors and Panels: Extensive colour choice from any major laminate supplier in large sheet size. Top rail/Hardware/Door Furniture - AA10 satin anodised requiring minimum maintenance. Polyester powder coating is an optional extra.
- Seating: Changing cubicles include optional cantilever seat or standard seat bracket. Seats are made of melamine faced particle board with an aluminium edge, with solid grade laminate and wood as options.
- Installation: Helmsman offers a full installation service for its products.

**HELMSMAN also provide an extensive range of lockers and changing room furniture.**

**After-sales Service:** All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email [service@helmsman.co.uk](mailto:service@helmsman.co.uk)

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

