



METAL LOCKERS

SPECIFICATION



HELMSMAN



Key Features:

Attractive and functional locker design for dry areas.

Sizes: 1775H x 300W x 450D, 1775H x 380W x 450D, 1775H x 450W x 450D

Other sizes also available on request.

Please allow up to 4mm tolerance per locker.

Sturdy construction with body and door frame made with heavy gauge mild steel of press formed channel section.

Doors also manufactured from mild steel.

Each door is fitted with a Camlock or Hasp and Staple lock, as required. Other options are available.

Extensive range of colours and finishes available.



NBS



Barbour
PRODUCT SEARCH



MADE IN
BRITAIN

1 Northern Way

Bury St Edmunds

Suffolk

IP32 6NH

(+44) 01284 727626

sales@helmsman.co.uk

www.helmsman.co.uk

METAL LOCKERS

SPECIFICATION

SUPPLYING
LEISURE
AND THE
EDUCATIONAL
INDUSTRY WITH
LOCKERS FOR
OVER
70 YEARS

Construction

1-6 Compartments available. Powder Coated Mild Steel, spot welded and pop riveted.

Nesting

Depending on size, lockers can be supplied as single units or nested in groups during the manufacturing process.

Door

Full length door stiffeners for extra door rigidity and two 'five knuckle' semi-concealed hinges.

Lock

Each door is fitted with a Camlock or Hasp and Staple lock as standard.

Hooks

Lockers are supplied with plastic hooks located on each side of the compartment (one & two compartments only).

Rails

Coat rails are fitted in locker compartments 300mm deep and over (one & two compartments only)

Numbering

Doors can be fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder. Maximum of 4 numbers. Other numbering options are available.

Colours

Body is powder coated in colour 'Ice' as standard, colour options for doors can be selected from Helmsman's standard range.

Stands/Seats

Lockers can be provided with either stands or stands with seats on request.

Helmsman can also offer installation. Please ask the sales team for more information.

We're happy to match other specifications or bespoke requirements.

