BENCH SEATING

SPECIFICATION

HELMSMAN





Key Features:

Attractive and modern seating for dry areas.

Sizes:
Bespoke sizing is designed to suit the individual project.

Sturdy construction with carcass manufactured from mild steel - powder coated.

Slats will be manufactured from an Ash hardwood.

Extensive range of colours and finishes available.

1 Northern Way
Bury St Edmunds
Suffolk
IP32 6NH
(+44) 01284 727626
sales@helmsman.co.uk
www.helmsman.co.uk

NBS Barbour PRODUCT SEARCH Constructionline CHAS MADE IN BRITAIN

BENCH SEATING

SPECIFICATION

Variety of Bench Seating Options Available

Island Benching
Free standing bench, optional shoe tray

Single Sided Bench
Available with coat hook bar

Double Sided Bench
Freestanding with coat hook bar

Cantilever Seating
Depending on the strength of the wall. Bracket is recommended every 500mm.

Wall to Floor Seating
Fixed to either wall or floor or both. Bracket is recommended every 500mm.

Material
Manufactured from 40mm x 40mm or 25mm x 25mm mild steel tubes. Slats are made from Ash Hardwood.

Fixings
Adjustable feet with concealed floor fix.

Size
Made to measure.

Colours
The frame is powder coated in the colour 'Ice' as standard, other RAL colour options are available.

Coat Hook Bars
Wall-mounted coat hook bar with 5 hooks as standard. Bespoke options are available.

Optional Extras include Installation, shoe trays, foot bars and lockers with integrated seat stands. Slats can be made from 10/12mm Solid Grade Laminate.
Please ask our Sales Team for more information.

We're happy to match other specifications or bespoke requirements.

SUPPLYING LEISURE AND THE EDUCATIONAL INDUSTRY WITH LOCKERS FOR OVER 70 YEARS