



BENCH SEATING

SPECIFICATION



Key Features:

Attractive and modern seating for wet areas.

Sizes:

Bespoke sizing designed to suit the individual project.

Sturdy construction with carcass manufactured from zinc-plated mild steel - powder coated.

Slats will be manufactured from an Ash hardwood.

Extensive range of colours and finishes available.



NBS



Barbour
PRODUCT SEARCH



Constructionline



MADE IN
BRITAIN

1 Northern Way
Bury St Edmunds
Suffolk
IP32 6NH

(+44) 01284 727626
sales@helmsman.co.uk
www.helmsman.co.uk

BENCH SEATING

SPECIFICATION

SUPPLYING
LEISURE
AND THE
EDUCATIONAL
INDUSTRY WITH
LOCKERS FOR
OVER
70 YEARS

Variety of Bench Seating Options Available

Island Benching

Free standing bench, optional shoe tray

Single Sided Bench

Available with coat hook bar

Double Sided Bench

Freestanding with coat hook bar

Cantilever Seating

Depending on the strength of the wall. Bracket is recommended every 500mm.

Wall to Floor Seating

Fixed to either wall or floor or both. Bracket is recommended every 500mm.

Material

Manufactured from 40mm x 40mm mild steel section. The frame is zinc-plated for a wet environment. Slats in Ash hardwood.

Fixings

Adjustable feet with concealed floor fix.

Size

Made to measure.

Colours

The frame is powder coated in colour 'Ice' as standard, other RAL colour options are available.

Coat Hook Bars

Wall-mounted coat hook bar with 5 hooks as standard. Bespoke options are available.

Optional Extras include Installation, shoe trays, foot bars and lockers with integrated seat stands. Slats could be made from 10/12mm Solid Grade Laminate.

Please ask our Sales Team for more information.

We're happy to match other specifications or bespoke requirements.